

ADM-2121AX

21.5" 250 Nits NEMA 4X Display, PoE & Projected Capacitive Touch



- 21.5" Active Matrix TFT LCD Display
- Resolution up to 1920 x 1080
- Integrated HDMI & USB Extender; Video signal transmission length up to 330 ft (100m) over CAT5e cable
- NEMA 4X/Waterproof Stainless Steel Enclosure
- Projected Capacitive Touch
- HDBaseT 5Play extends audio, video, control, Ethernet, and power over a single Cat5e/ Cat6 cable

Model Name	ADM-2121AX-00A
Display Size	21.5 inch
Resolution (Max)	1920 x 1080
Aspect Ratio	16:9
Response time (Typical)	14 ms
Contrast Ratio	1000:1
Brightness (Max)	250 nits
Video Input	HDMI via Transmitter
Touch Screen	Projected Capacitive
USB	2 x USB 2.0
Touch Interface	via Transmitter
OS Support	Windows XP, Windows 7 & up
Power Requirement (Max)	powered by Transmitter
Power Consumption (Max)	21 W
Recommended Power Supply	29 W
Heat Dissipation	70 BTU/hr
Mounting	Pedestal/VESA/Wall/Ceiling/Benchtop
Net Weight	20 Lbs/ 9.07 kg
Dimension (WxHxD)	22.89 x 13.74 x 1.93 inch 581.4 x 348.9 x 49.1 mm
Operating Temp	0~50°C (32~122°F)
Storage Temp	-20~60°C (-4~140°F)
Humidity	5% to 95% non-condensing
Nema 4X	SS 304/316L
Rating	meet NEMA 4X/ IP66
Certification	N/A

Standard Dimensions

